

## FRESCOLORI® pure

Delivery and servicing surfaces exclusively by trained FRESCOLORI® processing specialists, with a long-term guarantee of high quality.

Delivery and servicing surfaces exclusively by trained FRESCOLORI® processing specialists, with a long-term guarantee of high quality. Noble and impervious, like a mirror. A world of splendour Seen from close up, the last structures dissolve – as if the view slips into the depths. A unapproachably smooth surface, which still longs to be touched.

<b>Material:</b>	1 CM5 layer 1 CM3 layer Wax soap
<b>Consumption:</b>	CM5 about 0.9 kg/m <sup>2</sup> each layer CM3 about 0.5 kg/m <sup>2</sup> each layer Wax soap, about 0.06 kg/m <sup>2</sup>
<b>Colour:</b>	freely selectable
<b>Application:</b>	Indoor

Surfaces are prepared and primed.

- Application of the first layer of the CARAMOR® limestone-marble plaster, in grain thickness 5,. Uniform application strictly observed.
- Observe the waiting times, with a rest period until the first layer is dry.
- Application of the second layer of the CARAMOR® limestone-marble plaster, in grain thickness 3
- Observe the quite short waiting time (touch dry)
- Humidify the surface with a long bristle brush/spray bottle with water, and prevent any running of the water on the surface
- Design freedom: light or strong smoothing of the surface
- Observe the uniform distribution of the effluent limestone milk
- After short drying, polish with a trowel
- Carefully sand the corners and edges the next day
- Apply the wax with a trowel
- Polish the surface with a polishing machine, provided with a lambskin covered disk, and sand after a waiting period of approx. 1 hour.