

FRESCOLORI® stone XL

Delivery and servicing surfaces exclusively by trained FRESCOLORI® processing specialists, with a long-term guarantee of high quality.

A fascination in stone - matte and puristic, concentrated on the essentials: the expression of an aesthetic lifestyle, a natu- ral atmosphere and a striking spatial effect. What else could better provide for a similar sensory experience of protection and security? Stone XL - our limestonemarble plaster in combination with additionally added mica effect - for punctual glossy effects.

Material: 1 CM7 layer

1 CM7G layer

ETC

Consumption: CM7 about 1.2 kg/m² each layer

CM7G about 1.8 kg/m² each layer

ETC, about 0.08 kg/m²

Colour: freely selectable

Application: Indoor

Surfaces are prepared and primed.

- Application of the first layer of the CARAMOR® limestone-marble plaster, in grain thickness 7
- Observe the waiting times, with a rest period until the first layer is dry.
- Application of the second layer of the CARAMOR® limestone-marble plaster, in grain thickness 7, with added mica
- Observe the quite short waiting time (touch dry)
- Humidify the surface with a long bristle brush/spray bottle with water, and prevent any running of the water on the surface
- Instant smooth the surface with a trowel, by applying a uniform pressure
- Observe the uniform distribution of the effluent limestone milk
- Respect the waiting times with a rest period until the next day
- Surface with polishing machine (grain size 180)
- Application of the ETC protection with a brush
- Polish the surface with a polishing machine provided with a lambskin covered disc